

**NEW**

**ELMO**

# EV-4400AF

## VISUAL PRESENTER



**The Visual Presenter incorporates the latest in high technology & user friendly control level and the most convenient way of use.**

- 18x optical powered zoom with Auto focus/iris
- Digital image magnification and scrolling
- Max. 420x310mm (16.5x12.2") wide shooting area
- More than 470 TV lines high resolution & better than 48dB S/N
- Built-in baselight for transparency/slide film viewing
- Twin upper lighting unit for even and bright illumination
- Operation via front panel, wireless remote control (supplied), mouse (supplied) or RS-232C terminal
- 5" LCD monitor (optional) attachable
- Audio input/output and microphone input
- Auto/push-set white balance control
- Nega/posi, color/B&W conversion
- Internal/external sync
- OSD (on screen display) control
- Flat stage body with foldable camera arm and carrying handle

**All these in one model - ELMO EV-4400AF**


# VISUAL PRESENTER EV-4400AF

## SPECIFICATIONS

Image pick-up device	1/3" IT CCD 410,000 pixels
Resolution (Horizontal)	More than 470TV lines
S/N ratio	More than 48dB
Lens : Zooming	18x zoom
: F No	2.1-2.4
: f (mm)	4.7-84.6
Close-up lens	Built-in (one-touch flip on-off)
Shooting area (VxH)	420x310mm - 26x20mm (16.5"x12.2"-1.0"x0.8")
Head rotation (front-rear)	Built-in (245°)
Iris	Auto (with level adjustment)
Zooming	Powered
Electronic zooming	Provided
Focusing	Auto focus/Powered focus
White balance	Auto/Push-set
Nega./Posi. conversion	Provided
Color/B&W selection	Provided
Edge enhancement	Provided
Enlargement of the image	Yes (Image from internal camera only)
Scroll	Yes (Image from internal camera only)
On screen display	Provided
Sync. system	Internal/External (Horizontal & Vertical)
Input selection	Internal/AV1/AV2
Composite video output	2 (One each of BNC & RCA connectors)
S-Video output	1 (Mini DIN 4 pin connector)
Audio output	Stereo (RCA connectors)
Microphone input	Provided
Composite video input	x2
S-Video input	x2
Audio input	x2 (stereo)
Upper lighting unit	Built-in (6W x2)
Baselight	Built-in
DC12V output	Provided (for optional LCD monitor)
Wireless (IR) remote control	Supplied
Mouse control	Supplied
Communication	RS-232C
Flat stage	Provided
Carrying handle	Built-in
Weight	10 kgs (22.1lbs)
Power source	AC120V 60/50Hz
Power consumption	0.5A

Note : Dimensions and weight are approximate.  
Design and specifications are subject to change without prior notice.

## PROFILE



## ELMO ELMO CO., LTD.



Rio de Janeiro • RJ • Rua Senador Dantas, 23/G. 201 Fds • Centro • CEP: 20.031-200 • Tel/Fax: (21) 2532-6036  
 São Paulo • SP • Rua Gomes Carvalho, 892 Cj.9798 • Vila Olímpia • CEP: 04.547-003 • Tel/Fax: (11) 3845-7722  
 Home Page: [www.cenario.com.br](http://www.cenario.com.br) • e-mail: [comercial@cenario.com.br](mailto:comercial@cenario.com.br)